

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 January 2001 (18.01.2001)

PCT

(10) International Publication Number
WO 01/04016 A1

(51) International Patent Classification⁷: **B65D 47/24**

LK, LS, MN, MW, NZ, SD, SG, SL, SZ, TT, TZ, UG, ZA, ZW); UNILEVER NV [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL).

(21) International Application Number: PCT/EP00/06252

(22) International Filing Date: 3 July 2000 (03.07.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/350,608 . 9 July 1999 (09.07.1999) US

(71) Applicant (for IN only): **HINDUSTAN LEVER LIMITED** [IN/IN]; Hindustan Lever House, 165/166 Backbay Reclamation, Mumbai 400 020, Maharashtra (IN).

(71) Applicant (for AE, AG, AU, BB, BZ, CA, CY, GB, GD, GH, GM, IE, IL, KE, LC, LK, LS, MN, MW, NZ, SD, SG, SL, SZ, TT, TZ, UG, ZA, ZW only): **UNILEVER PLC** [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB).


(72) Inventors: **GIBLIN, Edward, John**; Unilever Research U.S. Inc., 45 River Road, Edgewater, NJ 07020 (US). **GERHART, Mark, Douglas**; 869 Four Seasons Road, Westminster, MD 21157 (US). **TREPINA, George, Richard**; 346 Cove Harbur East, Holland, OH 43528 (US). **HAFFNER, Eugene, Francis**; 6905 North River Road, Waterville, OH 43566 (US).

(71) Applicant (for all designated States except AE, AG, AU, BB, BZ, CA, CY, GB, GD, GH, GM, IE, IL, IN, KE, LC,

(74) Agents: **ROTS, Maria, Johanna, Francisca et al.**; Unilever PLC, Colworth House, Patent Department, Sharnbrook, Bedford, Bedfordshire MK44 1LQ (GB).

[Continued on next page]

(54) Title: SPIGOT ASSEMBLY FOR CONTAINER



(57) Abstract: The present invention relates to a container (20) for liquids such as heavy-duty detergents, fabric softeners and the like. The opening (90) of the container comprising a valve (116) in fluid communication with the opening and adapted to be secured to the container by a separate collar (106).

WO 01/04016 A1



(81) **Designated States (national):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

- 1 -

SPIGOT ASSEMBLY FOR CONTAINERBACKGROUND OF THE INVENTION

5 There has been a surge in popularity of the so-called "club" stores wherein consumers often purchase goods in larger quantities than has typically been the custom. The popularity of these outlets and the increased demand for larger volume units for selling consumer products has led to
10 a need for improved packaging.

The need for updated packaging is particularly difficult to satisfy for heavy duty liquid detergents and other liquid consumer products since the weight of the enhanced volume of
15 liquid product poses formidable challenges to the packaging engineer. For instance, despite its larger size the package must still permit convenient dispensing by consumers, who range in age from children through middle aged adults and up into the older population. In addition, with the larger
20 volume of liquid product, the difficulties in ensuring structural integrity of the package are markedly increased. Moreover, it is desirable to provide such packaging at a low cost to consumers.

25 Various containers for carrying larger volumes of liquids by consumers are known.

Prior to the invention of the present invention, Chilton Products, Chilton, Wisconsin 53014 sold a 320 fluid ounce
30 container (2.5 gallons) having a top wall with a centrally disposed handle, a vent opening and cap on one side of the

- 2 -

handle and a dispensing opening and closure on the other side of the handle.

Prior to the invention of the present invention, a product
5 called "Tide with Bleach Alternative" was sold in a 300 fluid ounce container having in a top wall, a centrally disposed handle, a vent and vent closure on one side of the handle and a spigot covered with a measuring cup on the other side of the handle.

10

SUMMARY OF THE INVENTION

The present inventors have discovered an ergonomic, convenient-to-use container for liquids such as heavy duty
15 detergents, fabric softeners and the like.

In a first embodiment, the container includes a dispensing opening, a closure and a plurality of walls. At least one of the walls includes a non-uniform surface structured so
20 that the dispensing closure can be disposed on the surface when the container is in its dispensing position. In a still preferred embodiment, the non-uniform surface is etched into the wall, preferably by etching into the mold which forms the wall. In a still more preferred embodiment,
25 the closure is a measuring cup. The non-uniform surface preferably assists in retaining the measuring cup on the wall even if the wall is comprised of a material, such as thermoplastic, which would otherwise promote sliding of the closure on the wall in the event of any movement of the
30 container.

- 3 -

In another preferred embodiment, the top wall of the container includes a vent, a vent cap forming a closure for the vent, a handle, a pouring aperture and a pouring closure covering the pouring aperture. The top surfaces of the vent cap, the handle and the pouring closure are generally parallel, and the height of the top surfaces of the vent cap and the pouring closure are within an inch of the height of the top surface of the handle. The presence of generally parallel surfaces at the top of the container which are of the same or similar height promotes stacking of the shipping containers, since an uneven effective top surface of the container would tend to result in uneven stacking. Preferably, the closure for the pouring aperture includes a measuring cup.

15

In another preferred embodiment, the top wall of the container includes a handle extending from a handle base within the top wall. A pouring aperture is surrounded by a pouring aperture base which also extends from the top wall. In accordance with this preferred aspect of the invention, the pouring aperture base is isolated from the interior handle base by the handle base exterior. By isolating the interior handle base areas from the base of the pouring aperture, it can be expected that if any residual liquid product is present in the pouring aperture base area after the container has been used, the isolation of such area from the interior handle area will diminish the likelihood that liquid product will find its way to the handle and inconvenience the consumer.

30

- 4 -

In another preferred embodiment, the invention comprises a valve assembly which preferably includes at least two separate pieces, (i) a valve and (ii) a collar for securing the valve to the container. The invention also comprises a container having the valve assembly. The valve may include a base, a valve head, a valve stem and a resilient valve actuator.

In its preferred form, the container of the invention includes in its top wall, a medial handle, a pouring aperture and over-fitting measuring/closure on one side of the handle, and a vent opening and vent cap on the opposite side thereof. Preferably the container includes at least six sides, more preferably at least eight sides, to enhance structural stability while at the same time permitting use of the minimal amounts of resin and other structural components possible. The at least 8 sides are believed to provide structural strength and bulge resistance.

In another preferred embodiment, the handle is generally curved, which applicants anticipate will result in improved compressive strength. It is believed that the presence of soft radii rather than sharp radii will enhance the compressive strength of the container, particularly relative to containers in which the handle contains sharp angles.

For a more complete understanding of the above and other features and advantages of the invention, reference should be made to the following Detailed Description of Preferred Embodiments and to the accompanying drawings.

- 5 -

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of a container according to the invention.

5 Fig. 2 is a side elevational view of the container of Fig. 1.

Fig. 3 is a top plan view of the container of Fig. 1.

Fig. 4 is a cross section along the lines of 4-4 of Fig. 2.

10 Fig. 5 is a front elevational view of the container of Fig. 1.

Fig. 6 is a rear elevational view of the container of Fig. 1.

Fig. 7 is a bottom plan view of the container of Fig. 1.

Fig. 8 is a cross section along the lines of 8-8 of Fig. 7.

15 Fig. 9 is an exploded view of the pouring aperture, the pouring base, the pouring finish, the valve assembly and the valve collar of the invention.

Fig. 10 is a partial elevational view showing particularly the pouring opening, spigot and measuring cup/closure of the invention.

20 Fig. 11 is a cross section along the lines 11-11 of Fig. 10.

Fig. 12 is a cross section along the lines 12-12 of Fig. 10.

Fig. 13 is a cross sectional view along the lines 13-13 of Fig. 10.

25 Fig. 14 is a perspective view of the bottle of Fig. 1 in the pouring position.

Fig. 15 is a cross section illustrating the venting of product through the vent hole and vent cap of the present invention.

30 Fig. 16 is a cross section illustrating the pouring of product through the spigot of the present container.

- 6 -

DETAILED DESCRIPTION OF THE INVENTION

Container or bottle 20 includes top wall 22, front wall 24, side walls 26, 28, 30, 32, 34 and 35, and rear wall 36.

5

Bottom wall 38 supports the container.

Top wall 22 includes a recessed area 40 in which is disposed valve or spigot apparatus 42 and closure/measuring cup 44, which will be described in greater detail below. Medially disposed with respect to valve or spigot assembly 42 is handle 46 which is integral with top wall 22. Handle 46 includes a base 48 having an interior aspect 50 and an exterior aspect 52. The interior of handle 46 is generally oval shaped as can be seen e.g., in Fig. 2.

Disposed laterally to handle 46 and on an opposite side from spigot assembly 42 is vent 56 and vent cap 58. The height of the highest point of wall 22 adjacent vent 56 is considerably higher than that in recessed area 40. Rear wall 36 includes oval etched area 60. The etching provides a non uniform or rough surface for reasons which will be discussed below.

As seen particularly in Fig. 2, the recessed area 40 in which the spigot assembly 42 is disposed is isolated from the interior aspect 50 of handle 46 by handle base 48. It is anticipated that isolation of the spigot area from the interior of the handle will prevent itinerant liquid product from migrating from the spigot area to the interior of the handle. This can be expected to make it less likely that

- 7 -

the consumer will find liquid product on his or her hand at the conclusion of the pouring operation.

As can be seen especially in Fig. 2, the top surfaces of measuring cup 44, handle 46, and vent cap 58 are generally parallel. Moreover, the heights of the top surfaces of the measuring cup 44 and the vent cap 58 are independently within one inch of the top surface of handle 46, especially within $\frac{1}{4}$ of an inch of the top surface of handle 46, and most preferably within $\frac{1}{8}$ inch of the top surface of the handle 46. Keeping the top surfaces parallel and at approximately the same height facilitates the stacking of containers in that the effective top surface of the container seen by a container stacked on top of it will be more or less even whereby to prevent uneven stacking of the containers.

The large oval handle aperture 70 facilitates gripping of the container by the consumer; there are no uneven edges to cause the consumers discomfort. This is particularly important given the substantial weight which the container is designed to contain.

The handle and top wall of the container body include several features which it is believed contribute to an improved compressive strength. The forward and rear walls 210, 212 of the handle are generally curved rather than having rectilinear sides which meet at relatively sharp angles with each other or with the top wall 22. That is, the handle of this aspect of the present invention comprises arcs or substantially straight lines connected by arcs

- 8 -

rather than substantially straight lines intersecting other substantially straight lines to form sharp angles. This refers not merely to the edges of the handle on the inside and outside surfaces but also to angles which would be
5 formed at intersections of imaginary midlines, such as midline 310, of the handle. Thus the handle should have arcs rather than sharp angles both on its inside and outside surfaces as well as at the intersections of imaginary midlines. Moreover, the base 48 of the handle at its front
10 is immediately adjacent the base of the pouring opening, so it is disposed in an area of the top wall having a particularly sturdy structure.

Other features believed relevant to compressive strength
15 include the fact that the base of the handle 48 at its front is in contact with the top wall of the container at a large number of points, extending e.g., from reference 214 on one side to 216 on the other, so that any force transmitted from above will be dissipated rather than concentrated at a few
20 points. This is believed to make the container top wall, and therefore the container as a whole, less susceptible to failure. Indeed the width of the base at the handle's front end (measured along a horizontal axis, e.g., parallel to the top surface of the measuring cup/valve closure) is at least
25 twice the width of the handle, preferably at least three times, still more preferably at least four or five times the width of the handle (also measured along a horizontal axis). In addition, the rear end of the handle merges curvedly with the elevated top wall 22 adjacent to the vent cap so that,
30 again, any force transmitted from the handle is dissipated over a large area rather than concentrated at a few points.

- 9 -

As can be seen from the figures, the preferred package includes eight vertically extending side panels, including the front and rear walls. Use of six or more, especially use of eight or more side walls or panels is believed to enhance the compression strength of the container and to permit the use of less resource, e.g. thermoplastic polymers, in its manufacture. Use of less resource in manufacture in turn leads to less waste material after the useful life of the container is complete.

Referring especially to Figs. 7 and 8, bottom wall 38 includes outer rim 80 which comprises the primary support for the container. Heel 80 extends downwardly further than other aspects of the bottom wall 38. Wall 38 may include the base push-up construction shown in the Fig. 7 wherein an angled portion 82 is disposed inwardly of first ring 80 and medial aspect 84 of wall 38 is disposed further inwardly.

Parting line 86 (Fig. 7) is an artifact of container manufacture when the container is blow molded. Parting line 86 reflects the joining of two halves of the mold used to make the container. It may be desirable, as illustrated in Figs. 7 and 8, to have a rib 90 of enhanced thickness and length at the parting line to provide support when the weight of the liquid product pushes downwardly on the medial aspect 84 of bottom wall 38. In such circumstances, rib 90 will assist in supporting the weight of the product. The structural support rib along the middle of the push-up is known per se and is also called the "pinch-off." As the push-up inverts due to the weight of the liquid contents,

- 10 -

the rib may contact the flat surface and prevent further inversion of the push-up. Alternatively, there may be a series of parallel grooves in the bottle base's push-up to resist push-up inversion. The base push-up area may have
5 one or two horizontally extending tiers for added strength, or may be waffled for increased strength.

Referring particularly to Fig. 9, top wall 22 has disposed therein annular dispensing opening 90. Dispensing opening
10 90 is supported by base 92 and by finish 94. Base 92 is generally circular and may include a plurality of levels as is illustrated in Fig. 9. In at least one level, elongated tabs 96 which are equally spaced from each other along the circumference of the base, serve to mate with a bead on the
15 measuring cup, as will be described below. Below tab 96 a step 98 is provided in base 92 to support the measuring cup 44 when it is in place over the spigot assembly.

At the bottom of finish 94 are disposed two oppositely
20 positioned sets of ratchets 100. Finish 94 is also provided with external threads 102 for mating with internal threads 104 on valve securement collar 106. Top thread 108 includes mirror image wedges 110, 112 which serve to facilitate alignment of valve base 114 when the spigot is in place by
25 providing lug confining walls.

Valve base 114 includes spigot or valve 116, valve support column 118, spigot support platform 120, outer ring 122 and inner depending ring 124. Spigot support 114 is placed
30 within dispensing aperture 90 by snap fitting inner ring 124 within the mouth of aperture 90. Outer ring 122 includes

- 11 -

one or more oppositely disposed depending lugs 130, which are accommodated in a space between each of the mirror image wedges 110, 112. This facilitates the proper alignment of spigot supporting structure 114 and ultimately of spigot 116.

Spigot 116 includes a valve mechanism of a type available from the Davis S. Smith Worldwide Dispensers of Merton, London of Great Britain. The spigot comprises spigot housing 134 resilient actuating button 136, valve stem 138, valve stem gripper 148 and valve 140. Operation of this simple valve is best seen with reference to Figs. 14 and 16. In order to dispense product, the consumer rests the container on front wall 24 by pivoting the container forward along the front section of ring 80 of bottom wall 38. The consumer dispenses product by pressing the resilient actuator button 136, which receives valve stem 138 in circular retaining structure, gripper 148. Preferably, gripper 148 is also resilient and slightly narrower than the diameter of the valve stem 148. The force applied by the consumer's finger is transmitted through valve stem 138 and forces valve 140 away from valve seat 150. This permits product to flow through the spigot and into the wash, or more preferably, into measuring cup 44.

Gripping wings 160, 162 are disposed on either side of valve housing 134 to permit the consumer to grasp the valve housing with two fingers while applying pressure with the thumb.

- 12 -

As best seen in Figs. 9 and 13, the spigot assembly 116 is secured to bottle finish 94 by spigot or valve collar 106. Internal threads 104 mate with external threads 102 on the bottle finish. Opening 170 on the spigot collar permits the
5 spigot to extend outside of the collar. The top of the spigot collar includes flange 172 which rests upon outer ring 122 of the spigot base when the collar is secured in place on the spigot finish. Depending wall 176 of the spigot collar includes in addition to internal threads 104,
10 lugs 178 which mate with ratchet 100 at the bottom of the spigot finish to secure more or less permanently the collar to the container.

The outside of spigot collar 106 may be provided with
15 vertically extending ribs 180 to assist in rotating the collar when it is applied to the container.

To facilitate dispensing of product, it is preferred that the container include a vent 56 and vent cap 58. The
20 container may also be filled through the vent, if so desired. Vent 56 comprises vent finish 166 which is threaded with external thread 168 to mate with internal thread 170 on vent cap 58. As best seen in Fig. 15, loosening of vent cap 58 permits air to flow inwardly, as
25 illustrated by the arrows in Fig. 15, and thereby to replace with air the volume of product lost when product is dispensed. In the illustrated embodiment, the vent opening finish is externally threaded and its external threads mate with internal threads on the vent closure. Alternatively,
30 the vent closure may be a push/pull closure, disc-top or snap-top closure. Preferably, the cap employs a linerless

- 13 -

seal (e.g., valve seal). However, the venting closure may have either a lined or linerless seal and have either a continuous thread or an interrupted thread to assist in venting air into the bottle upon slight twisting. The venting closure may have an anti-removal lug stopping against a lug on the bottle finish, such engagement occurring after $\frac{1}{4}$ to $\frac{1}{2}$ turns to loosen the closure.

It will be appreciated that when the container is in its dispensing position resting on front wall 24, it may be desirable to rest momentarily measuring cup 44. Particularly in view of the anticipated large volume of the container, it will be tempting to rest the measuring cup on one of the walls of the container, especially the wall opposite the wall on which the container is resting. Since it is envisioned that the container may be made of a material, such as certain thermoplastics, which is relatively smooth, in accordance with the invention, a non uniform section may be provided within one of the walls to assist in maintaining the cup in its position while it is disposed on the container. An example is illustrated in Fig. 14 wherein surface 60 which has a racetrack-like periphery, has been etched into rear wall 36. This is expected to minimize any tendency of measuring cup 44 to slip or slide on the surface of the container. Front panel 24 includes a large flat area to provide a stable base and to resist rocking during the dispensing operation. The side of the bottle adjacent the top vent closure becomes the top of the bottle in the dispensing position. This panel 36 is flat and level and has the textured surface wherein the

- 14 -

measuring cup can be placed between uses in the upright position.

Measuring cup 44 serves the dual function of measuring cup
5 and closure for the spigot assembly. Measuring cup 44 is
releasably secured to the container in its inverted position
by being snap fit over equi-spaced ribs or lugs 96, which
mate with bead 190 at the mouth of the cup. Alternatively,
the measuring cup can be secured to the bottle base finish
10 by use of a continuous thread to screw on the bottle base
finish or by other means.

The cup's annular bead and the bottle's three or more lugs
are designed to stay engaged during the impact of case
15 packing as well to as withstand the rigors of shipping and
warehousing without becoming dislodged.

The container may be mono-layer or multi-layer and may be
made of HDPE, PP, PVC, PET, POLYCARBONATE or acrylic or
20 nitrite base resins, and preferably contains a minimum of
25% PCR.

Preferably, the measuring cup has textured fill line bands
etched into the interior of the cup to aid the consumer
25 visually in filling to the proper dose. The measuring cup
may have a v-groove channel on the exterior of the mouth,
similar to a laboratory beaker, to aid in pretreating
strains with precise pouring. This channel could have an
anti-drip lip. Alternatively, there may be "V" or "U"
30 notches in the top side wall for a controlled pour.

- 15 -

If so desired, the measuring cup can include a handle. The measuring cup could have an exterior, annular anti-drip lip.

The container or bottle of the inventions may be pigmented
5 opaque or may be made clear by fabricating it from clarified grades of the aforementioned resins.

In addition to the vertical side panels, including the side panels at the vertical corner intersections, there may be
10 other strengthening vertical design features such as outer ribs or inner grooves either at the corner intersections or elsewhere in the side panels, or at in both locations.

The bottle, valve, valve collar and vent closure may be made
15 of anti-static grades of the aforementioned resins. The tap collar and vent closure are preferably made of a polyolefin resin, most preferably PP. Preferably, the pigmented tap body is the same color as the pigmented tap collar and vent closure. Alternatively, these components may be clear and
20 the measuring cup could be opaque.

Preferably, the front and back panels of the bottle include in-mold labels (IML labels), preferably plastic IML's. Plastic IML's may be opaque or clear. Polypropylene (PP)
25 IMLs may be used to reduce blistering given that the containers of the invention may have a relatively large label area. Alternatively, instead of an IML, there may be a stretch or shrink label which act like a "girdle" to resist bottle bulging with these labels. Also, the bottles
30 front/back panels may be waffled.

- 16 -

There may be indicia cut into the molds and/or embossed on the molded bottle and vent closure which give instructions on use.

5 In an alternative design, the vent closure and the second bottle neck finish are in the same horizontal place as said first neck finish. In this configuration, the measuring cup may be attached to lugs at the base of the second neck finish and positioned over the vent closure.

10

To avoid label scuffing, the base of the bottle could be larger in length and thickness than the label panel's greatest length and thickness, so that labels would not contact the walls of the corrugated shipping container or
15 the label of another bottle.

It should be understood of course that the specific forms of the invention herein illustrated and described are intended to be representative only as certain changes may be made
20 therein without departing from the clear teachings of the disclosure. Accordingly, reference should be made to the following appended claims in determining the full scope of the invention.

25

- 17 -

CLAIMS

1. A system comprising
 - a) an opening, and
 - 5 b) a valve in fluid communication with said opening and adapted to be secured to be a container by a separate collar.
2. The system according to claim 1 wherein said valve is a
10 spigot.
3. The system according to claim 1 or 2, wherein said collar includes threads which are complementary with threads on a container.
15
4. The system according to any preceding claim, wherein said opening is in a container and said valve includes a base and said base is secured to said container by said collar.
20
5. The system according to claim 4, wherein said collar includes an annular flange which retains the valve base on said container.
- 25 6. The system according to any preceding claim, wherein said valve includes a valve head, and a valve seat against which said valve head is urged when said valve is closed.
7. The system according to claim 6, wherein said valve head
30 is connected to a valve stem which is associated with a resilient valve actuator which urges said valve head against said valve seat when said valve is closed.

- 18 -

8. The system according to any preceding claim, wherein said valve includes one or more wings for grasping the valve.

5 9. The system according to any preceding claim, wherein said container has a neck and said opening is in said neck and said valve base is received within said opening.

10 10. The system according to claim 5, wherein said collar further comprises a cylindrical wall depending from said annular flange.

11. The system according to claim 1 further comprising a container in which said opening is disposed and wherein said
15 valve includes one or more depending lugs which are received within lug confining walls on a finish of said container.

12. The system according to claim 1 further comprising a container in which said opening is disposed and further
20 comprising ratchets on a finish of said container which act with complementary ratchets on said collar to lock said collar onto said container.

13. The system according to claim 3 further comprising a
25 container in which said opening is disposed and wherein said container threads are disposed on a finish of said container.

14. A valve assembly which comprises at least two separate
30 pieces, the first piece comprising a valve and the second comprising a collar for securing said valve to a container.

- 19 -

15. The valve assembly according to claim 14, wherein said valve is a spigot.

16. The valve assembly according to claim 14, wherein said
5 collar includes fastening threads.

17. The valve assembly according to claim 14, wherein said valve includes a base suitable for being secured to said container by said collar.

10

18. The valve assembly according to claim 14, wherein said collar includes an annular flange for retaining the valve base on said container.

15 19. The valve assembly according to claim 14, wherein said valve includes a valve head, and a valve seat against which said valve head is urged when said valve is closed.

20 20. The valve assembly according to claim 19, wherein said valve head is connected to a valve stem which is associated with a resilient valve actuator which urges said valve head against said valve seat when said valve is closed.

25 21. The valve assembly according to claim 14, wherein said valve includes one or more wings for grasping the valve.

22. The valve assembly according to claim 18, wherein said valve base includes a recess which receives said annular flange of said collar.

30

- 20 -

23. The valve assembly according to claim 18, wherein said collar further comprises a cylindrical wall depending from said annular flange.

5 24. The valve assembly according to claim 14, wherein said valve includes one or more depending lugs which are adapted to be received within at least one lug confining wall on a finish of said container.

10 25. The valve assembly according to claim 14 further comprising ratchets on said collar which are adapted to act with complementary ratchets on a finish on said container to lock said collar onto said container.

15 26. The valve assembly according to claim 16, wherein said collar threads are adapted to mate with container threads disposed on a finish of said container.

20 27. The valve assembly according to claim 14, which comprises at least four separate pieces, said pieces comprising a combined valve head and stem, a resilient valve actuator, a valve housing and a collar.

25 28. The valve assembly according to claim 14, wherein said valve and said collar are of the same color.

29. The system according to claim 7 or 20, wherein the valve actuator is a button.

- 21 -

30. The system according to claim 5, wherein said valve base includes an annular recess which receives said annular flange of said collar.

1/10




Fig.1.




Fig.2.

3/10




Fig.3.




Fig.4.

4/10




Fig.5.

5/10




Fig.6.

6/10




Fig.7.





Fig.8.

7/10

Fig.9.



8/10




Fig.10.

Fig.11.





Fig.12.

9/10




Fig.14.

10/10




Fig.13.




Fig.15.




Fig.16.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/06252

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B65D47/24

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B65D B67D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 06042 A A.D. 1913 (M. SMIRLE) 24 December 1913 (1913-12-24)	1-7, 10, 13-20, 23, 26, 27, 29 9
Y	the whole document	
Y	FR 1 442 004 A (SOCIETA PER AZIONI LAVORAZIONI CHIMICHE E IMBALLAGGI METALLICI) 24 August 1966 (1966-08-24) figures 1,3	9
X	WO 95 22504 A (LIQUI-BOX CORPORATION) 24 August 1995 (1995-08-24) page 7, line 7 -page 9, line 19 figures 1-13	1, 2, 4-8, 10, 14, 15, 17-21, 23, 29

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

17 October 2000

Date of mailing of the international search report

30/10/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Smolders, R

INTERNATIONAL SEARCH REPORT

Intern nal Application No
PCT/EP 00/06252

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 461 408 A (J. SHEPARD) 24 July 1984 (1984-07-24)	1,3-5, 10,13, 14, 16-18, 23,26 12,25
Y	column 3, line 23 -column 4, line 19 figures 1-5	
Y	US 5 143 237 A (L. LINDSEY ET AL.) 1 September 1992 (1992-09-01) column 2, line 45 -column 4, line 36 figures 1-7	12,25
A	US 3 584 834 A (O. REID ET AL.) 15 June 1971 (1971-06-15) the whole document	1,2,6-8, 14,15, 19-21, 27,29

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 00/06252

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB N06042 A		NONE	
FR 1442004 A	24-08-1966	NONE	
WO 9522504 A	24-08-1995	AU 713864 B AU 1919795 A BR 9506807 A CA 2183576 A EP 0745057 A JP 10502316 T US 5680970 A	09-12-1999 04-09-1995 30-09-1997 24-08-1995 04-12-1996 03-03-1998 28-10-1997
US 4461408 A	24-07-1984	NONE	
US 5143237 A	01-09-1992	NONE	
US 3584834 A	15-06-1971	GB 1234433 A	03-06-1971